


PRODUCT SPECIFICATION: **Cat 5e/Outdoor**

CROSS SECTION	COLOR & PACKAGING
----------------------	------------------------------



Insulation: PVC

Component: P1: Blue & White/Blue
P2: Orange & White/Orange
P3: Green & White/Green
P4: Brown & White/Brown

Jacket: Black (Pantone: black)

Packaging: 1000ft BMP Box

MARKING

Jacket Marking (White)

ICE CABLE SYSTEMS CATEGORY 5E 350MHz OUTDOOR ETL
VERIFIED TO TIA/EIA-568-B.2 E312434-22 (UL) CMX OUTDOOR
TYPE CMR OR c(UL)us CMG FT4 75C - APP: DATA PHONE - ROOM:
ENT KIT NK FAM LR DR POWD OFF POO PAT MBR MBA BR1 BR2
BR3 BR4 BR5 GAR GYM OTHER - WALL: N S E W - JACK: 1 2 3 4 5 6
USE: KPAD TPAD LAN TEL RoHS XXXX/XXXX FT
"XXXX/XXXX" Stands for Length. eg: 0000/1000; 0004/0996, etc.

PERFORMANCE

Electrical Characteristics: **(20°C)**
Voltage: 300 Volts RMS
Temperature: -20°C to 75°C
Dielectric Strength: AC-500V/1 Min

Mechanical Characteristics:
Test Object: Jacket
Test Material: PVC
Before Tensile Strength (kg/mmP²): ≥1.05

DESCRIPTION

Rated Voltage (V)	300
Rated Temperature (°C)	75
Product Standard Certification	c (UL) CMX OUTDOOR-TYPE CMR OR ETL US CMG
Flame test	CMR FT4

Application:
Telephone and other communication circuits such as voice, data, and audio for on-premise customer systems.

Reference Standard:
UL 444 & the customer's specification

CONSTRUCTION

Conductor:	Solid Bare Copper
Component: 4 Twisted Pair	8C
AWG	24
Construction (mm)	1/0.511
Solid Dia. (±0.005 mm)	0.511
Insulation:	PE
Nom. Thickness (mm)	0.19
Insulation Dia. (±0.05mm)	0.925
Ripcord:	210Dx6 nylon thread
Jacket:	Linear PE
Nom. Thickness (mm)	0.80
Outer Dia. (±0.10mm)	5.6



1521 Pontius Ave., Los Angeles, CA 90025
Email: info@icecable.com Web: <http://www.icecable.com>
Tel: 310.444.1950 Fax: 310.444.1966

REVISION HISTORY

Sample No.	-	Spec No.	51757-A
Revision	A		
Date	11/01/2009	Page	1 of 2
Designed by	Approved by		
BR	Brian Rizzo		



ELECTRICAL CHARACTERISTICS:

- a. Conductor resistance: Max. 9.38 ohms/100m at 20°C;
- b. D-C Resistance Unbalance: Max. 5%;
- c. Pair-to-Ground Capacitance Unbalance: Max. 330 pF/100m;
- d. Characteristic Impedance (1-100MHz): 100 +/- 15 ohms;
- e. Propagation Delay Skew (1-100MHz): Max. 45ns/100m;
- f. Mutual capacitance: 46-56 pF/M

Test report: Pair1=49.9pF/M. Pair2=49.6pF/M. Pair3=51.6pF/M. Pair4=49.1pF/M

g. Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB/100m)	ACR (dB)	PSNEXT (dB)	ELFEXT (dB)	PSELFEXT (dB/100m)	RL (dB)	DELAY (ns/100m)
0.772	1.8	67.0	65.2	64.0	66.0	63.0	19.4	575.0
1	2.0	65.3	63.3	62.3	63.8	60.8	20.0	570.0
4	4.1	56.3	52.2	53.3	51.7	48.7	23.0	552.0
8	5.8	51.8	46.0	48.8	45.7	42.7	24.5	546.7
10	6.5	50.3	43.8	47.3	43.8	40.8	25.0	545.0
16	8.2	47.3	39.1	44.4	39.7	36.7	25.0	543.0
20	9.3	45.8	36.5	42.8	37.7	34.7	25.0	542.0
25	10.4	44.3	33.9	41.3	35.8	32.8	24.3	541.2
31.25	11.7	42.9	31.2	39.9	33.9	30.9	23.6	540.4
62.50	17.0	36.4	19.4	35.4	27.8	24.6	21.5	538.6
100	22.0	35.3	13.3	32.3	23.8	20.8	20.1	538.0
200	32.4	30.8	-	27.8	17.8	14.8	18.0	536.6
300	41.0	28.2	-	25.2	14.3	11.3	16.8	536.1
350	44.9	27.2	-	24.2	12.9	9.9	16.3	535.9



1521 Pontius Ave., Los Angeles, CA 90025
 Email: info@icecable.com Web: http://www.icecable.com
 Tel: 310.444.1950 Fax: 310.444.1966

Sample No.	-	Spec No.	51757-A
Revision	A		
Date	07/28/2007	Page	2 of 2
Designed by	Approved by		
BR	Brian Rizzo		